

## PRIMAVERA 125 4T3V - TECHNICAL SPECIFICATIONS

|                                     |  |
|-------------------------------------|--|
| <b>ENGINE</b>                       | 3-valve 4-stroke single cylinder i-get catalysed   |
| <b>DISPLACEMENT</b>                 | 124 cc (155 cc)  |
| <b>BORE X STROKE</b>                | 52 mm x 58,6 mm (58 mm x 58,6 mm)  |
| <b>MAX POWER AT THE CRANK SHAFT</b> | 8,1 kW - 11 HP - a 8,000 rpm (9,2 kW - 12,5 CV- 7,750)                                   |
| <b>MAX TORQUE</b>                   | 10.4 Nm at 6,750 rpm (12.4 Nm a 6,750 rpm)   |
| <b>CONSUMPTION</b>                  | 40 km/l (37 km/l)  |
| <b>CO2 EMISSIONS COMPLIANCE</b>     | 60 g/km (63 g/km)  |
| <b>FUEL SYSTEM</b>                  | Electronic Injection   |
| <b>COOLING</b>                      | Forced air   |
| <b>STARTER</b>                      | Electric   |
| <b>GEARBOX</b>                      | CVT automatic with torque server   |
| <b>CLUTCH</b>                       | Automatic dry centrifugal with shock absorbers   |
| <b>LOAD-BEARING STRUCTURE</b>       | Sheet steel shell with welded structural reinforcements                                  |
| <b>FRONT SUSPENSION</b>             | Single arm with helical spring and hydraulic shock absorber                              |
| <b>REAR SUSPENSION</b>              | Helical spring with adjustable preload (4 positions) and single hydraulic shock absorber |
| <b>FRONT BRAKE</b>                  | Stainless steel Ø 220 mm disc with hydraulic control                                     |
| <b>REAR BRAKE</b>                   | Ø 140 mm drum with mechanical control  |
| <b>ABS/ASR SYSTEM</b>               | ABS at the front wheel only  |
| <b>FRONT TYRE</b>                   | Tubeless 110/70 - 12"  |
| <b>REAR TYRE</b>                    | Tubeless 120/70 - 12"  |
| <b>LENGTH/WIDTH/WHEELBASE</b>       | 1.870 / 735 / 1,340 mm   |
| <b>SEAT HEIGHT</b>                  | 790 mm   |
| <b>FUEL TANK CAPACITY</b>           | 8 litres   |
| <b>EMISSIONS COMPLIANCE</b>         | Euro 5   |