



## PRIMAVERA 125 3V TOURING – TECHNICAL SPECIFICATIONS

<b>ENGINE</b>	3-valve 4-stroke single cylinder i-get catalysed
<b>DISPLACEMENT</b>	124.5 cc
<b>BORE X STROKE</b>	52 mm x 58,6 mm
<b>MAX POWER AT THE CRANK SHAFT</b>	8.1 kW – 10.9 HP at 8,000 rpm
<b>MAX TORQUE</b>	10,4 Nm a 6.000 rpm
<b>CONSUMPTION</b>	113mpg
<b>CO2 EMISSIONS COMPLIANCE</b>	60g/km
<b>FUEL SYSTEM</b>	Electronic Injection
<b>COOLING</b>	Forced air
<b>STARTER</b>	Electric
<b>GEARBOX</b>	CVT automatic with torque server
<b>CLUTCH</b>	Automatic dry centrifugal with shock absorbers
<b>LOAD-BEARING STRUCTURE</b>	Sheet steel shell with welded structural reinforcements
<b>FRONT SUSPENSION</b>	Single arm with helical spring and single hydraulic shock absorber
<b>REAR SUSPENSION</b>	Helical spring with preload adjustable (4 positions) and single hydraulic shock absorber
<b>FRONT BRAKE</b>	Stainless steel Ø 200 mm disc with hydraulic control
<b>REAR BRAKE</b>	Ø 140 mm drum with mechanical control
<b>ABS/ASR SYSTEM</b>	ABS at the front wheel only
<b>FRONT TYRE</b>	Tubeless 110/70 - 12"
<b>REAR TYRE</b>	Tubeless 120/70 - 12"
<b>LENGTH/WIDTH/WHEELBASE</b>	1.870 / 735 / 1.340 mm
<b>SEAT HEIGHT</b>	790 mm
<b>FUEL TANK CAPACITY</b>	8 litres
<b>EMISSIONS COMPLIANCE</b>	Euro 5