



NEW BEVERLY 400 S - TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder 4-stroke, 4 valves
ENGINE CAPACITY	399 cc
BORE X STROKE	84 mm x 72 mm
POWER	26 kW @ 7,500 rpm
TORQUE	37.7 Nm @ 5,500 rpm
CONSUMPTION (WMTC CYCLE)	27 km/l
CO2 EMISSIONS	87 g/Km
VALVE TIMING SYSTEM	Single overhead camshaft (SOHC) - 4 valves
FUEL SYSTEM	Electronic injection
COOLING SYSTEM	Liquid
LUBRICATION	Wet sump
STARTER	Electric
GEARBOX	CVT continuously variable transmission
CLUTCH	Automatic centrifugal multiplate wet clutch
FRAME	Double cradle in high strength tubular steel
FRONT SUSPENSION	Hydraulic telescopic fork
REAR SUSPENSION	Dual hydraulic shock absorbers adjustable in preload
FRONT BRAKE	Ø 300 mm disc
REAR BRAKE	Ø 240 mm disc
BRAKING SYSTEM	ABS - ASR
FRONT TYRE	Tubeless 120/70 16"
REAR TYRE	Tubeless 150/70 14"
LENGTH / WIDTH / WHEELBASE	2.155 mm / 800 mm / 1.550 mm
FUEL TANK CAPACITY	12 l
EMISSIONS COMPLIANCE	Euro 5