

GTS SUPER 125 – TECHNICAL SPECIFICATIONS

ENGINE Single-cylinder, 4-stroke, 4 valves, electronic injection, i-get

ENGINE CAPACITY 125 cc

BORE X STROKE 52 mm x 58.7 mm

10.3 kW - 14 HP - at 8,750 rpm MAX POWER

MAX TORQUE 12 Nm at 6,750 rpm

CONSUMPTION 38.5 km/l

CO2 EMISSIONS

60 g/km **CERTIFICATION**

FUEL SYSTEM Electronic injection

> COOLING Liquid

IGNITION Electric Start & Stop system

TRANSMISSION CVT with torque server

CLUTCH Automatic dry centrifugal clutch with vibration dampers

LOAD BEARING

STRUCTURE

Sheet metal body with welded structural reinforcements

FRONT SUSPENSION Single-sided swingarm with coil spring and hydraulic control

Double hydraulic shock absorber with four-position spring pre-load **REAR SUSPENSION**

adjustment

FRONT BRAKE Hydraulically operated 220 mm stainless steel disc

REAR BRAKE Hydraulically operated 220 mm stainless steel disc

ABS/ASR SYSTEM As standard

FRONT TYRE Tubeless 120/70 - 12"

REAR TYRE Tubeless 130/70 - 12"

LENGTH / WIDTH /

WHEELBASE

1,980 / 765 / 1,385 mm

SEAT HEIGHT 790 mm

FUEL TANK CAPACITY 7 litres

EMISSIONS COMPLIANCE Euro 5+