

V9 BOBBER - TECHNICAL SPECIFICATIONS	
Engine	Transversal 90° V-twin, two valves per cylinder.
Cooling	Air
Displacement	853 cc
Bore and stroke	84 x 77 mm.
Maximum power	65 HP (47,8 kW) - 6.800 rpm (Also available at 35 kW, A2 driver license)
Maximum torque	73 Nm - 5.000 rpm
Compliance	Meets European Directive Euro 5.
Emissions	119 g/km (CO2)
Consumption	57.65 MPG
Gearbox	6 speed
Fuel Tank	15 I (4 reserve)
Seat Height	785 mm
Dry Weight	194 kg
Kerb Weight	210 kg (According to guideline VO (EU) 168/2013 with all fluids, with
Front suspension	standard equipment and fuelled with at least 90% of usable tank volume)
•	Hydraulic telescopic fork Ø 40 mm
Rear suspension	Swingarm Twin-sided with two spring preload adjustable shock absorbers
Front wheel	Lightweight alloy, 16" 130/90
Rear Wheel	Lightweight alloy, 16" 150/80
Front brake	Stainless steel floating disc Ø 320 mm, Brembo caliper with 4
	differentiated and opposed pistons.
Rear brake	Stainless steel disc Ø 260 mm, floating 2 pistons caliper.
Features	Full LED lights package with DRL, LCD dashboard, MGCT Moto Guzzi Traction, Standard double channel ABS.