



SXR 50 - TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder 4-stroke i-get
ENGINE CAPACITY	50 cc
BORE X STROKE	39 mm / 41.35 mm
MAX POWER	2.4 kW at 7000 rpm
MAX TORQUE	3.3 Nm at 6250 rpm
CONSUMPTION	41,6 km/l (WMTC Cycle)
CO2 EMISSIONS	57 g/km
DISTRIBUTION	Single overhead camshaft (SOHC) - 3 valves
COOLING	Forced air
POWER SUPPLY	Electronic injection
LUBRICATION	Wet sump
STARTING	Electrical
TRANSMISSION	Automatic continuously variable transmission (CVT) with torque server
CLUTCH	Automatic centrifugal dry clutch
CHASSIS	Single cradle structure in tubular steel with pressed reinforcements
FRONT SUSPENSION	Telescopic hydraulic fork, 76 mm stroke
REAR SUSPENSION	Dual action single shock absorber, adjustable to 5 positions
FRONT BRAKE	Ø 220mm brake disc served by 2 Ø 25.4 mm dual piston floating callipers
REAR BRAKE	140 mm drum
FRONT TYRE	Tubeless 120/70 - 12"
REAR TYRE	Tubeless 120/70 - 12"
LENGTH	1.965mm
WIDTH	803 mm
SEAT HEIGHT	775 mm
WHEELBASE	1.360 mm
FUEL TANK CAPACITY	7 litres
EMISSIONS COMPLIANCE	Euro 5