



NEW BEVERLY 300 S - TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder 4-stroke, 4 valves
ENGINE CAPACITY	278 cc (300cc)
BORE X STROKE	75 mm x 63 mm
POWER	19 kW @ 8,000 rpm
TORQUE	26 Nm @ 6,250 rpm
CONSUMPTION (WMTC CYCLE)	30.3 km/l
CO2 EMISSIONS	77 g/Km
VALVE TIMING SYSTEM	Single overhead camshaft (SOHC) - 4 valves
FUEL SYSTEM	Electronic injection
COOLING SYSTEM	Liquid
LUBRICATION	Wet sump
STARTER	Electric
GEARBOX	CVT continuously variable transmission
CLUTCH	Automatic centrifugal dry clutch
FRAME	Double cradle in high strength tubular steel
FRONT SUSPENSION	Hydraulic telescopic fork
REAR SUSPENSION	Dual hydraulic shock absorbers adjustable in preload
FRONT BRAKE	Ø 300 mm disc
REAR BRAKE	Ø 240 mm disc
BRAKING SYSTEM	ABS - ASR
FRONT TYRE	Tubeless 110/70 16"
REAR TYRE	Tubeless 140/70 14"
LENGTH / WIDTH / WHEELBASE	2.125 mm / 800 mm / 1.540 mm
FUEL TANK CAPACITY	12 l
EMISSIONS COMPLIANCE	Euro 5